



Robotics 2

Human-Robot Coexistence and Collaboration

Prof. Alessandro De Luca

DIPARTIMENTO DI INGEGNERIA INFORMATICA
AUTOMATICA E GESTIONALE ANTONIO RUBERTI



SAPIENZA
UNIVERSITÀ DI ROMA



Human-friendly robotics



The goal




traditional
robotics



replacing
humans




human-
friendly
robotics



collaborating
with humans



co-workers on factory floor



personal robots in service




SAPHARI concept

Place the human at the center of the entire robot development



FP7 ICT
EU project
(2011-15)



address all essential aspects of safe and intuitive **physical interaction** between humans and complex human-like robots in a strongly integrated way



Handling of collisions and intentional contacts


Basic **safety-related control** problems in physical Human-Robot Interaction (**pHRI**)




collision **detection/isolation** and **reaction**
(**without** the use of external sensing)



workspace monitoring
for **continuous**
collision **avoidance**
(while the task is running)



estimation and control
of **intentional forces**
exchanged at the contact
(**with** or **without** a **F/T** sensor)
for human-robot collaboration





Safe physical Human-Robot Interaction (pHRI)

Control architecture of consistent robot behaviors (De Luca, Flacco: IEEE BioRob 2012)



- **integrated design & use** of soft mechanics, actuation, (proprio- and exteroceptive) sensing, communication, and **control** algorithms



Physical HRI


Hierarchy of consistent behaviors

Safety

lightweight mechanical design
compliance at robot joints

Safety is the most important feature of a robot that has to work close to human beings

Classical solutions for preserving safety in industrial environments, i.e., using cages or stopping the robot in the presence of humans [**ISO 10218**], are inappropriate for pHRI





Physical HRI


Hierarchy of consistent behaviors

Safety

Coexistence

Coexistence is the robot capability of sharing the workspace with other entities, most relevant with humans

Human (and robot!) safety requirements must be always guaranteed (i.e., **safe coexistence**)



original robot task

sharing the workspace
without the need of physical contacts

safe HR coexistence



Physical HRI

Hierarchy of consistent behaviors




Collaboration occurs when the robot performs complex tasks with direct human interaction and coordination

Two modalities which are not mutually exclusive:
contactless and **physical**

↓
gestures or voice commands
visual coordination





↓
with intentional contact
and exchange of forces





Types of collaborative operations





From ISO 10218-1:2011 & 10218-2:2011 standards (refined in ISO-TS 15066:2016)







Qualification of our control architecture for pHRI

Relation with ISO Standard 10218 and Technical Specification 15066



	Speed	Separation distance	Torques	Operator controls	Main risk reduction
SAFETY Safety-rated monitored stop COEXISTENCE	Zero while operator in CWS	Small or zero	Gravity + load compensation only	None while operator in CWS	No motion in presence of operator
Hand guiding COLLABORATION	Safety-rated monitored speed	Small or zero	As by direct operator input	E-stop; Enabling device; Motion input	Motion only by direct operator input
Speed and separation monitoring COEXISTENCE	Safety-rated monitored speed	Safety-rated monitored distance	As required to execute application and maintain min separation distance	None while operator in CWS	Contact between robot and operator prevented
Power and force limiting COLLABORATION	Max determined by RA to limit impact forces	Small or zero	Max determined by RA to limit static forces	As required by application	By design or control, robot cannot impart excessive force

ISO 10218-1/2:2011
ISO/TS 15066:2016




- collision detection and reaction
- workspace sharing
 - with collision avoidance
- coordinated motions & actions
 - with/without contact



Control levels in the collision event pipeline

Haddadin, De Luca, Albu-Schäffer: IEEE T-RO 2017



Monitoring signals can be generated from sensors or models (signal- or model-based methods)

Context information is needed (or useful) to take the right or most suitable decisions



Collision detection and reaction

Residual-based experiments on DLR LWR-III (IROS 2006, IROS 2008)



- collision detection followed by different **reaction** strategies
- **zero-gravity** behavior: gravity is always compensated first (by control)
- detection time: **2-3 ms**, reaction time: **+ 1 ms**

3 videos



admittance mode

reflex torque

reflex torque

first impact at 60°/s

first impact at 90°/s

$$\dot{q}_r = K_Q r$$

$$\tau = K_R r$$



Coexistence

Early days and yesterday ...



1989

video

informational video by National Institute for Occupational Safety and Health (USA)

commercial video by ABB Robotics on EPS (Electronic Position Switch) and early SafeMove software



2012

video



Coexistence

Today and tomorrow? ...

SafeMove2

Safety certified monitoring of robot motion,
tool and standstill supervision

Nov 2016, Singapore

video

commercial video by ABB Robotics
of SafeMove2 software
(using 2 laser scanners)

<https://youtu.be/pIIhY8E3HFg>

2016

IROS 2013
Best Video Award Finalist



(using 1 Kinect
depth sensor)

video



Safe Physical Human-Robot Collaboration

Fabrizio Flacco Alessandro De Luca

Robotics Lab, DIAG
Sapienza Università di Roma






March 2013



Collision avoidance

Using exteroceptive sensors to monitor robot workspace (ICRA 2010)



- external sensing: stereo-camera, TOF, structured light, depth, laser, presence, ... placed optimally to minimize occlusions (robot can be removed from images)





Depth image

How to use it?





Cartesian space

A long process

Fusing multiple Kinects to survey human-robot workspaces

C. Lenz, M. Grimm, T. Röder, A. Knoll

Robotics and Embedded Systems
Technische Universität München

[video](#)

[TU Munich](#)



Configuration space

Possible, but typically only for few dofs

Real time control for safe human-robot coexistence using stereo vision



The manipulator performs the assigned task until an unknown obstacle is detected.



video

Univ Pisa



Depth space


A 2.5-dimensional space

- non-homogeneous 2.5 dimensional space
 - x, y position of the point in the image plane [pixel]
 - d depth of the point with respect to the image plane [m]
- depth space is modeled as a pin-hole sensor
- point in Cartesian reference frame $P_R = (x_R, y_R, z_R)$
- point in sensor frame $P_C = RP_R + t = (x_C, y_C, z_C)$
- point in depth space

$$p_x = \frac{x_C f s_x}{z_C} + c_x$$

$$p_y = \frac{y_C f s_y}{z_C} + c_y$$

$$d_p = z_C$$



gray areas
behind the obstacles



Depth space

Distance evaluation


- distance between a **point of interest** $\mathbf{P}_D = (p_x, p_y, d_p)$
and an **obstacle point** $\mathbf{O}_D = (o_x, o_y, d_o)$

$$\text{dist}(\mathbf{P}, \mathbf{O}) = \sqrt{v_x^2 + v_y^2 + v_z^2}$$


$$v_x = \frac{(o_x - c_x)d_o - (p_x - c_x)d_p}{fs_x} \quad v_y = \frac{(o_y - c_y)d_o - (p_y - c_y)d_p}{fs_y} \quad v_z = d_o - d_p$$



(if **obstacle** point is **closer** than point of interest, **set** $d_o = d_p$)



8 points of interest
on the robot






Repulsive vector

A version of artificial potentials


- **repulsive vector** generated from the distance vector $D(P, O) = (v_x, v_y, v_z)$

$$V_C(P, O) = v(P, O) \frac{D(P, O)}{\|D(P, O)\|}$$


$$v(P, O) = \frac{V_{max}}{1 + e^{\|D(P, O)\| (2/\rho)\alpha - \alpha}}$$



- repulsive vectors **due to all obstacles** near to point of interest are considered
 - **orientation** \Rightarrow sum of all repulsive vectors, **magnitude** \Rightarrow nearest obstacle only
 - inclusion of a **pivoting** strategy to avoid local minima or “too fast” obstacles



video





video



Obstacle velocity

The pivot method (similar to a vortex field)

- for moving obstacles that are faster than the control point (on the robot)



$$\mathbf{a} = \frac{\dot{\mathbf{V}}_R(\mathbf{P})}{\|\dot{\mathbf{V}}_R(\mathbf{P})\|}, \quad \mathbf{r} = \frac{\mathbf{V}_R(\mathbf{P})}{\|\mathbf{V}_R(\mathbf{P})\|}, \quad \beta = \arccos(\mathbf{a}^T \mathbf{r})$$

if $\beta < \frac{\pi}{2}$ then

$$\mathbf{n} = \mathbf{a} \times \mathbf{r}, \quad \mathbf{v} = \frac{\mathbf{n} \times \mathbf{a}}{\|\mathbf{n} \times \mathbf{a}\|},$$

$$\gamma = \beta + \frac{\beta - \frac{\pi}{2}}{1 + e^{-(\|\mathbf{V}_R(\mathbf{P})\|((2/\|\mathbf{V}_{R_{max}}) - 1)c)}}$$

$$\mathbf{V}_{R_{pivot}}(\mathbf{P}) = \|\mathbf{V}_R(\mathbf{P})\| (\cos \gamma \mathbf{a} + \sin \gamma \mathbf{v})$$

else

$$\mathbf{V}_{R_{pivot}}(\mathbf{P}) = \mathbf{V}_R(\mathbf{P})$$

end if





Motion control

Different handling of end-effector and other control points on the robot

- **end-effector** repulsive vector → repulsive velocity added to the original task velocity
- collision avoidance for the whole **robot body** (e.g., 8 control points)

- repulsive vector
- Cartesian constraints
- joint velocity limits modification (using SNS)



- fluid, **jerk-limited** motion → human feeling of safety


Reflexes
GmbH

www.reflexxes.com



Safe coexistence

Collision avoidance in depth space (BioRob 2012)



video



Safe coexistence

Collision avoidance in depth space (ICRA 2012, J. Intell. & Rob. Syst. 2015)

video



resuming a cyclic Cartesian task as soon as possible ...




Monitoring the workspace with two Kinects

... without giving away the depth space computational approach (RA-L 2016)

When a single camera is used the robot avoids occluded points even when generated by a far obstacle; the second camera will avoid this

video

https://youtu.be/Wlw_Uj_ooYI



real-time efficiency

algorithm extremely fast also with 2 devices: **300 Hz** rate (RGB-D camera has 30 fps)

problems solved by the second camera

- + eliminates collision with false, far away “shadow” obstacles
- + reduces to a minimum gray areas, thus detects what is “behind” the robot
- + relative calibration of the two Kinects is done off-line



SYMPLEXITY cell for robotized work on metallic surfaces


For abrasive finishing/fluid jet polishing tasks & for **human-robot** quality assessment



SYMPLEXITY H2020 FoF EU project (2015-18)

- **ABB IRB 4600-60** robot, with integrated SafeMove option
- certified communication with cell PLC, using ProfiSAFE protocol
- due to the intrinsic risks in the technological process, only for **HR coexistence** during visual check and measuring phase or for **contactless collaboration**
- **2 external** Kinects to recognize human gestures (e.g., automatic door opening, ...)
- **initially ... 2 internal** Kinects (placed at the top corners of the cabin) for monitoring human-robot distances

ABB



UNIMORE
UNIVERSITÀ DEGLI STUDI DI
MODENA E REGGIO EMILIA



SAPIENZA
UNIVERSITÀ DI ROMA





Additional safety hardware

Certified laser scanners to be used in parallel with the Kinects



SYMPLEXITY H2020 FoF EU project (2015-18)



- **two laser scanners** KEYENCE SZ-V 32n placed at calf height (~50 cm)
- maximize **coverage** of the free area inside the cell
- each sensor localizes the (radial) position of the operator in the cell, estimating an **approximate/conservative distance** to the robot
- **no missed situations**: robot slows down or stops according to sensed distance/area
- a **cascaded solution** of Kinects/laser scanners is a viable compromise between **certified safety** and **more flexible sharing** of the 3D workspace by human and robot







CAD robot model and equipment in depth images

Considering **CWS laser measuring device, cables** or other equipment in distance computation

CWS =
Coherent Wave Scattering



SYMPLEXITY H2020 FoF EU project (2015-18)




for each robotic set up, the suitable CAD model for depth space subtraction is loaded at start



Implemented control and communication architecture

Two **Kinects** for accurate HR distance monitoring, two **laser scanners** for backup safety






Safe coexistence in an industrial robotic cell

ABB IRB 4600 operation in an abrasive finishing cell with **human access**

video



video



depth images and GUI

- robot is moving at max 100 mm/s
- no safety zones were defined in ABB SafeMove
- Kinects **OK** (except when the view of one of the cameras is obstructed on purpose)





Collaboration

Contactless or physical



- in **contactless** collaboration, robot (or human!) actions are guided or follow from an exchange of information without physical interaction
 - this can be achieved via **direct communication**, e.g., with gestures and/or voice commands
 - or via **indirect communication**, by recognizing human intention or attention, e.g., through eye gaze
 - another form is **visual coordination** in which vision is used to coordinate human-robot relative motion
- in **physical** collaboration, there is an explicit and intentional contact with exchange of forces between human and robot
 - by measuring or **estimating contact forces**, the robot can predict human motion intention and react accordingly to it
 - collaborative tasks (e.g., human and robot carrying a heavy object) require **control of exchanged forces (and motion)** at the contact



Contactless collaboration

Using gesture and voice commands


- human body parts and gesture recognition



- speech recognition



voice
command




collaboration
starts



Human-robot communication

Using Kinect and SDK library

- the robot end-effector **position** is commanded by voice/gestures to **follow** (or **go to**) the human **left, right, or nearest hand**



video



Gesture communication in SYMPLEXITY cell

Using Kinect 2.0 RGB-D sensor, with built-in skeleton tracking



- initial 5 sec gesture to activate
- both hands **open** = start motion
- both hands **closed** = stop robot
- left closed + right open = limit speed
- left open + right closed = recover speed
- final gesture to deactivate





video



Visual coordination task

Dual formulations of human-robot relative tracking (IROS 2017)




- camera **on robot**, pointing to moving human head/face kept at a certain relative position

- camera **on human head**, with robot pointing to it and kept at a certain relative position

different Cartesian motion tasks of varying dimension $m \leq n$

cone represents a **relaxation** of the pointing task by some relative angle α_d






Simulation


Motion control using Task Augmentation method

- camera tracing a circle in a vertical plane, while pointing direction is kept constant

ROS environment, integrated with robot simulator V-REP



video





Experiment of visual coordination

KUKA LWR robot in ROS environment with FRI

<https://youtu.be/SRfpNrZD7k0>




Visual Coordination Task for Human-Robot Collaboration

Maram Khatib, Khaled Al Khudir, Alessandro De Luca



Robotics Lab, DIAG
Sapienza Università di Roma

March 2017



position error ≤ 5 cm pointing error < 0.03 rad

also in multi-sensory operation




video



Safe human-robot interaction


From coexistence to physical collaboration



parallel algorithm freq (Hz): 195.459
Repulsive velocity parallel: 0.000


video

coexistence through collision avoidance



<https://youtu.be/pllhY8E3HFg>

physical collaboration through contact identification (here, end-effector only)



video



parallel algorithm freq (Hz): 191.904
Repulsive velocity parallel: 0.443



Distance and contact point localization

Using Kinect, CAD model, and distance computation to **localize contact** (early 2014)

- **depth image** is acquired by a Kinect
- robot is removed from image (URDF filter by TUM), starting from its 3D CAD model
- human hand tracking on filtered image
- **3D CAD model of robot** and hand position are used to localize contact point on robot surface
- surfaces of robot links are modeled using polygonal patches
- 3D robot model is projected in workspace with a calibration matrix
- **distances are computed** between vertices of patches and the human hand
- ranges vary from about 20 cm (area of interest) down to 0 (contact)
- **residuals** are always zero when robot moves in free space






Distance and contact point localization

Use **residuals** to detect the contact event, also for multiple locations

- when the **residual** indicates a **contact/collision** (and colliding link), the **vertex** in the robot CAD surface model **with minimum distance** is taken as the **contact point**
- algorithm applied here in parallel to both **left** and **right** hand (no other body parts)




video



Improved contact point localization

Real-time localization using the CUDA framework (IROS 2017)

- the algorithm, based on distance computation in **depth space**, takes advantage of a **CUDA framework** for massively parallel **GPU** programming; **three 2.5D images** are processed:
 - real depth image I_r , captured by a RGB-D sensor (a Kinect)
 - virtual depth image I_v , containing only a projection of the robot CAD model
 - filtered depth image $I_f = f(I_r, I_v)$, containing only the obstacles



- parallel **distance computations** between **all robot points** in virtual image and **all obstacle points** in filtered image (same time needed to localize one or multiple contact points!)



Contact force estimation

Combining internal and external sensing

■ task

- localize (in the least invasive way) points on robot surface where contacts occur
- estimate exchanged **Cartesian** forces
- control the robot to react to these forces according to a desired behavior

■ solution idea

- use residual method to **detect** physical contact, **isolate** the colliding link, and **identify** the joint torques associated to the external contact force
- use a depth sensor to **classify** the human parts in contact with the robot and **localize** the contact points on the robot structure (and the **contact Jacobian**)
- **solve** a linear set of equations with the residuals, i.e., estimates of joint torques resulting from **contact wrenches** (**forces/moments**) applied anywhere to the robot

$$\mathbf{r} \simeq \boldsymbol{\tau}_{ext} = \mathbf{J}_c^T(\mathbf{q})\boldsymbol{\Gamma}_c = \left(\mathbf{J}_{L,c}^T(\mathbf{q}) \quad \mathbf{J}_{A,c}^T(\mathbf{q}) \right) \begin{pmatrix} \mathbf{F}_c \\ \mathbf{M}_c \end{pmatrix}$$



Contact force estimation

Some simplifying assumptions

- dealing with contact forces

- most **intentional** contacts with a single human part (hand, arm, fingers) are **not** able to transfer relevant **torques**
- to estimate reliably Γ_c we should have rank $\mathbf{J}_c = 6$, which is true only if the robot has $n \geq 6$ joints and the contact occurs at a link with index ≥ 6

assume  $\mathbf{M}_c = \mathbf{0}$

only a **pure Cartesian force** is considered

- dimension of the task related to the contact force is now $m = 3$ and its **estimation** is

$$\mathbf{r} \simeq \boldsymbol{\tau}_{ext} = \mathbf{J}_{Lc}^T(\mathbf{q}) \mathbf{F}_c \quad \longrightarrow \quad \hat{\mathbf{F}}_c = \left(\mathbf{J}_{Lc}^T(\mathbf{q}) \right)^\# \mathbf{r}$$

- the contact Jacobian can be evaluated once the contact point is detected by the external depth sensor that closely monitors the robot workspace
- this procedure represents a so-called **virtual force sensor**



Validation of virtual force sensor

Experiments in **static** conditions with the KUKA LWR 4 (IROS 2014)



- evaluation of estimated contact force


$$\hat{F}_c = \left(J_c^T(q) \right)^\# r$$

- estimation accuracy was initially tested using known masses in known positions
- a single mass hung either on link 4 or on link 7, to emulate a **single** (point-wise) contact

Link #	Mass	F_z	using J_{Lc}		using J_c	
			\hat{F}_z	Deviation	\hat{F}_z	Deviation
4	1.93	-18.93	-18.75	0.95%	-4.46	76.43%
7	1.93	-18.93	-18.91	0.1%	-18.82	0.58%

- a mass hung on link 7, and then a second on link 4 so as to emulate a **double** contact

Link #	Mass	F_z	\hat{F}_z	Deviation
4	2.03	-19.91	-19.43	2.41%
7	1.93	-18.93	-19.04	0.58%




case of two masses



On-line estimation of contact force

Used within an admittance control scheme (IROS 2014)

<https://youtu.be/Yc5FoRGJsrc>

A video thumbnail with a black background. At the top center is the Sapienza University of Rome logo. Below it, the title "Estimation of Contact Forces using a Virtual Force Sensor" is written in white. Underneath the title, the authors "Emanuele Magrini, Fabrizio Flacco, Alessandro De Luca" are listed. Below the authors, the department "Dipartimento di Ingegneria Informatica, Automatica e Gestionale, Sapienza Università di Roma" is mentioned. At the bottom center, the date "February 2014" is displayed.

**Estimation of Contact Forces
using a Virtual Force Sensor**

Emanuele Magrini, Fabrizio Flacco, Alessandro De Luca

Dipartimento di Ingegneria Informatica, Automatica
e Gestionale, Sapienza Università di Roma

February 2014



video



On-line estimation of contact force

Evolution of residuals, estimated forces, and compliant displacements

- control gains are chosen so as to assign a **stiff** behavior at a reference configuration
- at some time, human pushes on robot link 3
- due to the stiff robot behavior, a large force needs to be applied to move the robot
- when the hand is removed, the contact point returns smoothly to its initial position (zero error)




see slide #54 for the chosen **admittance control** scheme




Further validation of virtual force sensor

In static and **dynamic** conditions, using a hand-held F/T sensor (February 2019)

- comparing the F/T ground truth contact force measure with its residual-based estimation
 - with robot **at rest** (pushing)
 - in **robot motion** (hitting)



video



video

outgrowth of Emanuele Magrini's PhD thesis, May 2016



Estimation of contact force


Some limitations of the residual method

- **multiple** simultaneous contacts can be considered (e.g., with **both** human hands)

$$\begin{pmatrix} \hat{F}_1 \\ \hat{F}_2 \end{pmatrix} = (J_{L1}^T(q) \ J_{L2}^T(q))^\# r$$

but with much **less confidence** in the resulting force estimates (**detection is still ok**)

- **estimates** will be limited only to those components of F_c which can be detected by the residual (i.e., that produce work on robot motion)
- all **forces** $F_c \in \mathcal{N}(J_c^T(q))$ will never be recovered \Leftrightarrow they are 'absorbed' by the robot structure






Estimation of contact force

Sometimes, even **without** external sensing

- if contact is sufficiently “down” along the kinematic chain (≥ 6 residuals available), the estimation of **pure contact forces** does not need any external information ...







A closer analysis

Which force components are being estimated? Do we really need **external** sensing?


- a simple 3R planar case, with contact on different links



$$\text{rank} \{ \mathbf{J}_{c1} \} = 1$$



$$\text{rank} \{ \mathbf{J}_{c2} \} = 2$$



$$\text{rank} \{ \mathbf{J}_{c3} \} = 2$$

\mathbf{r} is a vector of dimension 3

$\hat{\mathbf{F}}_i$ { only **normal** force to link,
if contact point is known
(1 informative residual signal)

full force on link,
if contact point is known
(2 informative residuals)


full force on link, **even**
without knowing contact
(3 informative residuals)

- forces $\mathbf{F}_k \in \mathcal{N}(\mathbf{J}_k^T(\mathbf{q}))$ will **never** be recovered (**even** with known contact)



Additional F/T sensor at the base

Combining real & virtual sensors for estimating interaction forces/moments (IROS 2016)



KUKA 6-dof Agilus robot (@Augsburg)

- Recursive Newton-Euler Algorithm (fed by the residuals) for **ground force/moment** prediction
- comparison with **base F/T sensor readings**

(large) F/T sensor mounted at the base




Table of **possible options/improvements** for a contact wrench $\mathbf{W}_{ext,l} = (\mathbf{F}_{ext,l}, \mathbf{M}_{ext,l})$

- an external wrench acting on **link l** will only affect the first l components of $\boldsymbol{\tau}_{ext}$
- effect of \mathbf{F}_{ext} on $\boldsymbol{\tau}_{ext}$ depends on point \mathbf{p}_l while that of \mathbf{M}_{ext} does not, since **only** the contact link is relevant (isolated by residual)

	l	Known \mathbf{p}_l	Unknown \mathbf{p}_l with pure contact force
\mathbf{F}/\mathbf{T} sensor at the base	any	Estimate $\mathbf{W}_{ext,l}$	Estimate $\mathbf{F}_{ext,l}$ and \mathbf{p}_l
\mathbf{F} sensor at the base	any	Estimate $\mathbf{F}_{ext,l}$	Estimate $\mathbf{F}_{ext,l}$
	≥ 3	Estimate $\mathbf{W}_{ext,l}$	Estimate $\mathbf{F}_{ext,l}$ and \mathbf{p}_l
No sensor at the base	≥ 6	Estimate $\mathbf{W}_{ext,l}$	Estimate $\mathbf{F}_{ext,l}$ and \mathbf{p}_l





Collision or collaboration?

Distinguishing **hard/accidental** collisions and **soft/intentional** contacts

- using suitable **low** and **high** bandwidths for the residuals (first-order stable filters)

$$\dot{r} = -K_I r + K_I \tau_K$$

- a **threshold** is added to prevent false collision detection during robot motion



video



Collaboration control

Use of estimate of the external contact force for control (e.g., on a Kuka LWR)

- shaping the robot dynamic behavior in specific **collaborative tasks** with human
 - joint carrying of a load, holding a part in place, whole arm **force** manipulation, ...
 - robot motion controlled by
 - **admittance** control law (in **velocity FRI** mode)
 - **force, impedance** or **hybrid force-motion** control laws (needs **torque FRI** mode)
- all implemented **at contact level**
- e.g., admittance control law using estimated contact force (as in video of slide #46)
 - the scheme is realized at the single (or first) contact point
 - desired **velocity** of contact point taken proportional to (**estimated**) contact force

$$\dot{\mathbf{p}}_c = \mathbf{K}_a \mathbf{F}_a, \quad \mathbf{K}_a = k_a \mathbf{I} > 0$$

$$\mathbf{F}_a = \hat{\mathbf{F}}_c + \mathbf{K}_p (\mathbf{p}_d - \mathbf{p}_c), \quad \mathbf{K}_p = k_p \mathbf{I} > 0$$




initial contact point position when interaction begins




Contact force regulation with virtual force sensing

Human-robot collaboration in **torque control mode** (ICRA 2015)

- contact force estimation & control (**anywhere/anytime**)



video



see **ICRA 2015**

trailer (at 3'26''):


<https://youtu.be/glNHq7MpCG8> (Italian); https://youtu.be/OM_1F33fcWk (English)




Impedance-based control of interaction

Reaction to contact forces by generalized impedance — at **different** levels


consider a fully rigid robot



Joint impedance
needs joint torque sensors



Cartesian impedance
needs F/T sensor



Contact point impedance
without force/torque sensing, with estimation of contact force




Control of generalized impedance

HR collaboration at the contact level (ICRA 2015)

natural (unchanged) robot inertia **at the contact**

$$M_d = \left(J_c M^{-1} J_c^T \right)^{-1}$$

video




contact force **estimates** are used here
only to detect and localize contact
in order to start a collaboration phase

assigned robot inertia **at the contact**

with different apparent masses along **X, Y, Z**

video



contact force **estimates** used **explicitly** in
control law to modify robot inertia at the contact
($M_{d,X} = 20$, $M_{d,Y} = 3$, $M_{d,Z} = 10$ [kg])




Control of generalized contact force

Direct force scheme


- explicit **regulation** of the **contact force** to a desired value, by imposing

$$M_d \ddot{\mathbf{x}}_c + K_d \dot{\mathbf{x}}_c = K_f (F_d - \hat{F}_c) = K_f e_f$$

- a force control law needs always a measure (here, an **estimate**) of contact force
- **task-compatibility**: human-robot contact direction vs. desired contact force vector



$$F_{d,x} = 0, \quad F_{d,y} = 15N, \quad F_{d,z} = 0$$



video

however, *drift effects* due to poor control design





Control of generalized contact force

Task-compatible force control scheme (ICRA 2015)

- only the **norm** of the desired contact force is controlled along the **instantaneous direction** of the **estimated** contact force

$$F_{d,x} = 15 \frac{\hat{F}_{c,x}}{\|\hat{\mathbf{F}}_c\|}, \quad F_{d,y} = 15 \frac{\hat{F}_{c,y}}{\|\hat{\mathbf{F}}_c\|}, \quad F_{d,z} = 15 \frac{\hat{F}_{c,z}}{\|\hat{\mathbf{F}}_c\|} \quad \Leftrightarrow \quad \|F_d\| = 15 \text{ [N]}$$

- in static conditions, the force control law is able to regulate contact forces **exactly**



video

task-compatible control of contact force




Collaboration control

Hybrid force/velocity control scheme (ICRA 2016)

- it allows to control **both** contact force and motion in **two** mutually independent sub-spaces
- extends at the contact level a hybrid force/velocity control law, with the orientation of **contact task frame** being determined instantaneously
- task frame obtained by a rotation matrix R_t such that z_t is aligned with the **estimated** contact force

$$R_t = \begin{bmatrix} u & v & w \end{bmatrix} = \begin{bmatrix} u & v & \frac{\hat{F}_c}{\|\hat{F}_c\|} \end{bmatrix}$$



- after feedback linearization with $\tau = Ma + n - J_c^T \hat{F}_c$, the acceleration command is

$$a = J_c^\# M_d^{-1} (R_t a_c + M_d (\dot{R}_t^t \dot{x}_c - \dot{J}_c \dot{q})) + P_c \ddot{q}_0$$

- **complete decoupling** between force control and velocity control can be achieved by choosing the new auxiliary control a_c input as

$$a_c = S_f^c \ddot{y}_f + S_v^c \dot{v}$$



Collaboration control

Hybrid force/velocity control scheme

- the force regulation task should be along the instantaneous direction of the applied external force while the motion control task lives in the orthogonal plane
- the **selection matrices** are chosen as

$$\mathbf{S}_f^c = \begin{bmatrix} 0 \\ 0 \\ 1 \end{bmatrix} \quad \mathbf{S}_\nu^c = \begin{bmatrix} 1 & 0 \\ 0 & 1 \\ 0 & 0 \end{bmatrix}$$

- regulation of the contact force** to desired constant value $F_d > 0$ is obtained choosing

$$\ddot{y}_f = k_f \left(F_d - \|\widehat{\mathbf{F}}_c\| \right) - k_{df} \dot{y}_f$$

- control of the desired velocity** can be achieved using

$$\dot{\boldsymbol{\nu}} = \dot{\boldsymbol{\nu}}_d + \mathbf{K}_d (\boldsymbol{\nu}_d - \boldsymbol{\nu}) + \mathbf{K}_i \int_0^t (\boldsymbol{\nu}_d - \boldsymbol{\nu}) ds,$$

- the final control acceleration input becomes

$$\mathbf{a} = \mathbf{J}_c^\# \mathbf{M}_d^{-1} \left[\mathbf{R}_t \mathbf{S}_f^c (k_f e_f - k_{df} \dot{y}_f) + \mathbf{R}_t \mathbf{S}_\nu^c (\dot{\boldsymbol{\nu}}_d + \mathbf{K}_d \dot{\boldsymbol{\nu}} + \mathbf{K}_i e_\nu) \right. \\ \left. + \mathbf{M}_d \dot{\mathbf{R}}_t^c \dot{\mathbf{x}} - \mathbf{M}_d \dot{\mathbf{J}}_c \dot{\mathbf{q}} \right] + \mathbf{P}_c \ddot{\mathbf{q}}_0,$$




Collaboration control

Hybrid force/velocity control at contact level (IROS 2016)



- desired contact force along **Y direction** regulated to $F_d = 15[N]$
- constant desired velocity to perform a **line** in the **vertical XZ plane**

$$\boldsymbol{v}_d = \begin{bmatrix} 0.015 \\ 0.03 \end{bmatrix} \quad \dot{\boldsymbol{v}}_d = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$$

<https://youtu.be/tlhEK5f00QU>



video






Collaboration control




Hybrid force/velocity control at contact level (IROS 2016)

- desired contact force along the **X direction** regulated to $F_d = 15[N]$
- desired velocity/acceleration to perform a **circle** in the **vertical YZ plane**

$$\mathbf{v}_d = \begin{bmatrix} \omega \rho \sin \omega t \\ \omega \rho \cos \omega t \end{bmatrix} \quad \dot{\mathbf{v}}_d = \begin{bmatrix} \omega^2 \rho \cos \omega t \\ -\omega^2 \rho \sin \omega t \end{bmatrix}$$



video









Validation of collaboration control with a F/T sensor

Force and hybrid force/velocity control schemes at contact level (February 2019)

- desired contact force along the **estimated contact direction** regulated at 15 N
- ... and trajectory control with constant speed along a circle in the **orthogonal plane**



video



task-compatible force control: only the norm of the contact force is regulated to a desired value (15 N)

video




SYMPLEXITY cell for laser polishing

Including a manual polishing station with **human-robot physical collaboration**



SYMPLEXITY H2020 FoF EU project (2015-18)



Contact detection
(model-based) for **safety**

3D workspace monitoring
with 2 Kinects for
HR coexistence

Use of F/T sensor
and of residuals for
HR physical collaboration

Universal Robots UR10

- lightweight design
- CE safety certified

speed scaling/stop
from sensing HR distance
(= 0 in physical collaboration)
ISO/TS15066:2016



SAPIENZA
UNIVERSITÀ DI ROMA



Scenario for HRC in manual polishing


Preparing a metallic part for the final polishing by the laser machine

UR10 robot operation with HR coexistence/collaboration




part to be polished

video




measuring Berlin Heart part with the CWS




video

physical collaboration in contact

video



coexistence



video


coordination with LP machine

CWS = Coherent Wave Scattering (laser measurement of surface quality)



Scenario for HRC in manual polishing


Distinguishing different contact forces



- 6D Force/Torque (F/T) sensor at wrist
- manual polishing force is **measured**
 - end-effector Jacobian J_e is **known**

contact force at unknown location

- **not** measurable by the F/T sensor
- possibly applied by the human **while** manipulating the work piece held by robot
- contact Jacobian J_c is **not** known





Handling multiple contacts

Dynamic model and residual computation **using also the F/T sensor**

- robot **dynamic model** takes the form

$$M(q)\ddot{q} + \mathbf{S}(q, \dot{q})\dot{q} + g(q) = \tau + J_e^T(q)F_e + J_c^T(q)F_c$$

- joint torques resulting from different contacts

(measured) at the end-effector level

at a generic point along the structure

$$\tau_e = J_e^T(q)F_e$$

$$\tau_c = J_c^T(q)F_c$$

- monitor the robot generalized momentum $p = M(q)\dot{q}$
- (model-based) **residual vector** signal to detect and isolate the generic contacts

$$r(t) = K_i \left(p - \int_0^t (\mathbf{S}^T(q, \dot{q})\dot{q} - g(q) + \tau + \underbrace{J_e^T(q)F_e}_{\text{circled}} - r) ds \right)$$

$$K_i \rightarrow \infty \text{ (sufficiently large)} \Rightarrow r \simeq \tau_c$$



Admittance control strategy during manual polishing

Human and robot are physically collaborating

- when there is **no extra contact** along the structure, **position and orientation** of the end-effector are both held **fixed** by a **stiff kinematic control law**

$$\dot{q} = J_e^\# K_e \begin{pmatrix} v_r \\ \omega_r \end{pmatrix} = J_e^\# K_e \begin{pmatrix} I & 0 \\ 0 & T(\phi) \end{pmatrix} \begin{pmatrix} p_d - p \\ \phi_d - \phi \end{pmatrix}$$

as large as possible ↑ constant values

- in this way, the control law counterbalances all forces/torques applied by the operator **during manual polishing**
- when the human intentionally **pushes on the robot body**, control of the end-effector **orientation** is **relaxed**

$$J_e(q) = \begin{pmatrix} J_p(q) \\ J_o(q) \end{pmatrix}$$

3×6 for UR10

$$\dot{q} = J_p^\# K_p (p_d - p) + (I - J_p^\# J_p) K_r r$$

residual-based admittance reaction to extra contacts

- human can reconfigure the arm, thus **reorient the work piece** held by the robot



HRC phase with UR10 robot


Experimental verification in the lab (Mechatronics 2018)

https://youtu.be/slwUiRT_IJQ

video

video

<https://youtu.be/bjZbmlAclYk>



no F/T sensor, switch to **UR FreeDrive** mode

with F/T sensor, using our **residual** method


for a similar behavior with the KUKA LWR
see <https://youtu.be/TZ6nPqLPDxl>




HRC phase with UR10 robot

Experimental results (separating F/T measures from residuals)


both forces at the same time...



in all cases, no linear motion of EE position!




polishing force only...



extra force detected...

...joints move accordingly




...no joint motion

...joints move due to extra force only




Combining motor currents and F/T sensor data

Enhanced flexible interaction by filtering, thresholding, merging signals (ICRA 2019)



video



collaborative forces at E-E


ATI Mini45 F/T sensor

video

Robot in cyclic motion between four Cartesian positions

intentional contacts and/or collisions may occur anywhere

6-dof KUKA KR5 Sixx with closed control architecture and RSI interface at $T_c = 12$ ms





Our team at DIAG

Robotics Lab of the Sapienza University of Rome (back in 2014)



Acknowledgements

@Sapienza – DIAG - Gabriele Buondonno, Lorenzo Ferrajoli, **Fabrizio Flacco[†]**,
Claudio Gaz, Milad Geravand, Emanuele Magrini, Eleonora Mariotti, Raffaella Mattone

@DLR – Institute of Robotics and Mechatronics - Alin Albu-Schäffer, Sami Haddadin

@Stanford – Artificial Intelligence Lab - Oussama Khatib, Torsten Kröger



References - 1

Download pdf for personal use at www.diag.uniroma1.it/deluca/Publications

- A. De Luca and R. Mattone, “Sensorless robot collision detection and hybrid force/motion control,” IEEE Int. Conf. on Robotics and Automation, pp. 999-1004, 2005.
- A. De Luca, A. Albu-Schäffer, S. Haddadin, and G. Hirzinger, “Collision detection and safe reaction with the DLR-III lightweight manipulator arm,” IEEE/RSJ Int. Conf. on Intelligent Robots and Systems, pp. 1623-1630, 2006.
- S. Haddadin, A. Albu-Schäffer, A. De Luca, and G. Hirzinger, “Collision detection and reaction: A contribution to safe physical human-robot interaction,” IEEE/RSJ Int. Conf. on Intelligent Robots and Systems, pp. 3356-3363, 2008 (**IROS 2008 Best Application Paper Award**).
- A. De Luca and L. Ferrajoli, “Exploiting robot redundancy in collision detection and reaction,” IEEE/RSJ Int. Conf. on Intelligent Robots and Systems, pp. 3299-3305, 2008.
- A. De Santis, B. Siciliano, A. De Luca, A. Bicchi, “An atlas of physical human-robot interaction,” Mechanism and Machine Theory, vol. 43, no. 3, pp. 253–270, 2008 (**2017 MMT Award for Excellence**).
- A. De Luca and L. Ferrajoli, “A modified Newton-Euler method for dynamic computations in robot fault detection and control,” IEEE Int. Conf. on Robotics and Automation, pp. 3359-3364, 2009.
- F. Flacco, A. De Luca, “Multiple depth/presence sensors: Integration and optimal placement for human/robot coexistence,” IEEE Int. Conf. on Robotics and Automation, pp. 3916-3923, 2010.
- F. Flacco, T. Kröger, A. De Luca, and O. Khatib, “A depth space approach to human-robot collision avoidance,” IEEE Int. Conf. on Robotics and Automation, pp. 338-345, 2012.
- A. De Luca and F. Flacco, “Integrated control for pHRI: Collision avoidance, detection, reaction and collaboration,” 4th IEEE RAS Int. Conf. on Biomedical Robotics and Biomechatronics, pp. 288-295, 2012 (**BioRob 2012 Best Paper Award**).
- M. Geravand, F. Flacco, and A. De Luca, “Human-robot physical interaction and collaboration using an industrial robot with a closed control architecture,” IEEE Int. Conf. on Robotics and Automation, pp. 3985-3992, 2013.
- E. Magrini, F. Flacco, and A. De Luca, “Estimation of contact force using a virtual force sensor,” IEEE/RSJ Int. Conf. on Intelligent Robots and System, pp. 2126-2133, 2014.
- F. Flacco, T. Kröger, A. De Luca, and O. Khatib, “A depth space approach for evaluating distance to objects —with application to human-robot collision avoidance,” J. of Intelligent & Robotic Systems, vol. 80 S.1, pp. 7-22, 2015.



References - 2

Download pdf for personal use at www.diag.uniroma1.it/deluca/Publications

- E. Magrini, F. Flacco, and A. De Luca, "Control of generalized contact motion and force in physical human-robot interaction," IEEE Int. Conf. on Robotics and Automation, pp. 2298-2304, 2015 (ICRA 2015 Best Conference Paper Award Finalist).
- G. Buondonno and A. De Luca, "Combining real and virtual sensors for measuring interaction forces and moments acting on a robot," IEEE/RSJ Int. Conf. on Intelligent Robots and Systems, pp. 794-800, 2016.
- E. Magrini and A. De Luca, "Hybrid force/velocity control for physical human-robot collaboration tasks," IEEE/RSJ Int. Conf. on Intelligent Robots and Systems. pp. 857-863, 2016.
- F. Flacco and A. De Luca, "Real-time computation of distance to dynamic obstacles with multiple depth sensors," IEEE Robotics and Automation Lett., vol. 2, no. 1, pp. 56-63, 2017.
- M. Khatib, K. Al Khudir, A. De Luca, "Visual coordination task for human-robot collaboration," IEEE/RSJ Int. Conf. on Intelligent Robots and Systems, pp. 3762-3768, 2017.
- E. Magrini, A. De Luca, "Human-robot coexistence and contact handling with redundant robots," IEEE/RSJ Int. Conf. on Intelligent Robots and Systems, pp. 4611-4617, 2017.
- S. Haddadin, A. De Luca, and A. Albu-Schäffer, "Robot collisions: A survey on detection, isolation, and identification," IEEE Trans. on Robotics, vol. 33, no. 6, pp. 1292-1312, 2017.
- C. Gaz, A. De Luca, "Payload estimation based on identified coefficients of robot dynamics --with an application to collision detection," IEEE/RSJ Int. Conf. on Intelligent Robots and Systems, pp. 3033-3040, 2017.
- C. Gaz, E. Magrini, A. De Luca " A model-based residual approach for human-robot collaboration during manual polishing operations," Mechatronics, vol. 55, pp. 234-247, 2018.
- E. Mariotti, E. Magrini, A. De Luca, "Admittance control for human-robot interaction using an industrial robot equipped with a F/T sensor," IEEE Int. Conf. on Robotics and Automation, pp. 6130-6136, 2019.
- E. Magrini, F. Ferraguti, A.J. Ronga, F. Pini, A. De Luca, F. Leali, "Human-robot coexistence and interaction in open industrial cells," Robotics and Computer-Integrated Manufacturing, vol. 61, 101846, 2020.
- **Videos:** YouTube channel [RoboticsLabSapienza](https://www.youtube.com/channel/UC...). Playlist: [Physical human-robot interaction](https://www.youtube.com/playlist?list=PL...)